

File #: 2655 Date: January 28, 2025

Sarah Wilhelm

Wellington County 74 Woolwich Street Guelph, Ontario, N1H 3T9

Brett Salmon Town of Centre Wellington 1 MacDonald Square, Elora, Ontario, NOB 1S0

Dear Ms. Wilhelm and Mr. Salmon:

Re: Preliminary Servicing and Stormwater Management Brief 6586 Beatty Line North Township of Centre Wellington County of Wellington

SCS Consulting Group Ltd. has been retained by Sorbara/Tribute Brubacher Holdings Inc. to prepare a Preliminary Servicing and Stormwater Management Brief (PSSB) for a proposed development located at 6586 Beatty Line North (referenced as the "Subject Lands"), in the Township of Centre Wellington, County of Wellington.

This PSSB has been prepared in support of an Official Plan Amendment (OPA) for the Subject Lands. The effects of the OPA are to redesignate the Subject Lands and to expand the boundaries of the North West Fergus Secondary Plan (NWFSP) in the Township of Centre Wellington (TOCW) Official Plan (OP). The proposed OPA will augment the County-level May 2024 Settlement Area Boundary Expansion (SABE) Request. The instrument will establish permissions for serviced, urban-type land uses on the Subject Lands in conformity with the minimum density targets of the County of Wellington OP, the TCW OP, and the NWFSP. In doing so, the OPA will assist the County and Township in meeting their residential growth targets by the 2051 planning horizon. The Subject Lands are contemplated for inclusion within the Fergus Settlement Area Boundaries to permit urban-type residential uses. The Subject Lands would form a logical extension of the Storybrook Subdivision, which is located to the south, consisting of low and medium density residential uses, a park, and a stormwater management (SWM) pond.

The Subject Lands are located on the west side of Beatty Line North, south of the Beatty Line North and Sideroad 15 intersection, and directly north of Fergus and Elora-Salem's delineated urban settlement area (**Figure 1**). The Subject Property is approximately 43.2 hectares in size, rectangular in shape and has approximately 300 metres of frontage along Beatty Line North. It

File #: 2655 December 20, 2024 Page 2 of 9

is currently vacant except for one single-detached dwelling and an abandoned railway traverses through the Subject Lands in a northwest/southeast direction. Phases 2A+ and 2B of the existing Storybrook Subdivision are located immediately south of the Subject Lands (refer to **Figure 1** below).



Figure 1 – Site Location (Welling County Interactive Maps, 2024)

The Subject Lands consist primarily of agricultural lands with three (3) wetlands and one (1) headwater drainage feature (HDF). The proposed development is located in the Irvine Creek subwatershed of the Grand River watershed. As such, development of the Subject Lands is under the jurisdiction of the Grand River Conservation Authority (GRCA) with the wetlands and HDF regulated by GRCA under Ontario Regulation (O. Reg.) 41/24. Refer to **Figure 2**, below for the regulated areas of the Subject Lands.

File #: 2655 December 20, 2024 Page 3 of 9



Figure 2 – O. Reg. 41/24 Regulation Limit (GRCA, 2024)

Existing Topography and Drainage

The majority of the Subject Lands generally drain southerly towards the Storybrook Phase 2A+ subdivision (refer to **Figure 1**), via an existing draw to the south of the abandoned railway corridor that bisects the site. Refer to Catchment 101 on **Figure 3**. Elevations throughout the site range from approximately 415 m to 420 m.

Drainage from Catchment 101, approximately 22.89 ha in size, in addition to drainage from external lands to the north (Catchment EXT1 on **Figure 3**), is captured at Elliot Avenue West and conveyed southerly through the Storybrook Phase 2A+ and 2A lands (refer to **Figure 1**) via an existing concrete box bypass sewer. The storm sewer was designed and constructed to convey the 100 year pre-development flow of 2.546 m³/s from an area of 42.09 ha towards an existing woodlot located approximately 410 m south of the Subject Lands.

The design of the bypass sewer is detailed in the following reports and drawings with relevant excerpts included in **Attachment A**:

- Functional Servicing and Stormwater Management Report, Storybrook Subdivision prepared by R. J. Burnside & Associates Limited, December 2016, Revised February, 2018;
- Stormwater Management Report, North Pond, Storybrook Subdivision, Phase 1, R.J. Burnside & Associates Limited, April 2017;
- SWM Pond Conformance and Water Balance Submission, Storybrook Subdivision Phase 2A Draft Plan No. 23T-16003, SCS Consulting Group Ltd., December 2019;
- North SWM Pond Conformance Memo, Storybrook Subdivision Phase 2A+, SCS Consulting Group Ltd., March 2021; and,
- General Plan (Drawing No. 101), Storybrook Subdivision Phase 2A+, SCS Consulting Group Ltd., September 2021.

The southwestern and southern corners of the Subject Lands drain south and southeasterly, respectively, under existing conditions. These two areas, identified as Catchments 102A and 102B on the attached **Figure 3**, approximately 6.30 ha and 1.30 ha in size, respectively, sheet drain through adjacent lands to a tributary to the Grand River located off-site.

The remainder of the Subject Lands, identified as Catchment 103 on the attached **Figure 3**, approximately 12.77 ha in size, drains easterly to the HDF and wetland located in the southeastern corner of the site adjacent to Beatty Line. The HDF conveys the flows southeasterly, crossing Beatty Line approximately 200 m south of the Subject Lands via an existing culvert.

Proposed Grading

Due to the generally flat nature of the site, it is anticipated that the site will generally require fill import to sufficiently convey drainage and provide adequate cover over the proposed servicing. This condition is also driven by the requirement to convey the future storm drainage to the existing 1800 mm x 900 mm concrete box bypass sewer. All efforts will be made to minimize fill import where possible. Refer to the attached Conceptual Grading Plan (**Figure 4**) for more details.

Proposed Storm Drainage

Stormwater conveyance will be provided through a combination of a municipal storm sewers sized to convey the 5 year storm and an overland flow system within the municipal right-of-way (ROW) and easements, if necessary. Most of the Subject Lands will drain to a proposed SWM facility located in the south corner of the site which will outlet to the existing 1800 mm x 900 mm concrete box bypass sewer along Elliot Avenue West constructed as part of Phase 2A+ of the



File #: 2655 December 20, 2024 Page 5 of 9

Storybrook Subdivision (Outlet 1 on **Figure 3**). As noted above, the bypass sewer was sized to convey the pre-development 100 year flows from the Subject Lands, and outlets to the existing woodlot adjacent the Nichol Drain in Storybrook Phase 2B. Major system emergency spill from the Subject Lands (Regional storm event), is proposed to be directed to the Elliot Avenue ROW and conveyed via the ROW through the Storybrook Subdivision to the Nichol Drain.

External drainage from Catchment EXT1 will continue to drain to the central wetland on-site and will be directed southeasterly along the abandoned railway corridor, as shown on **Figure 5**. It is proposed to capture and convey the flows by a new clean water bypass sewer connecting to the existing 1800 mm x 900 mm concrete box bypass sewer (Outlet 1). Drainage from external Catchments EXT2 and EXT3 will continue overland towards the Subject Lands where it will then be conveyed via swale to the southwesterly and northeasterly wetlands, respectively, to maintain existing drainage conditions (refer to **Figure 4**). If the external lands develop in the future, the existing drainage patterns will need to be maintained in order to ensure feature-based water balance is achieved to all three wetlands.

Stormwater Management

Stormwater management (SWM) will be provided for the site per the Ministry of Environment, Conservation, and Parks (MECP), GRCA, and the Township of Centre Wellington design criteria. This will include a treatment train of Low Impact Development (LID) measures and an end-ofpipe wet SWM facility. The LID measures will provide quality and erosion control, as well as water balance benefits and may include increased topsoil depth, roof drains to grassed areas and/or soak-away pits, infiltration trenches, bioretention areas, etc. More detailed investigation into the feasibility and the location of the proposed LID measures will be undertaken as part of the functional SWM design completed in support of a Draft Plan of Subdivision application for the Subject Lands.

The proposed SWM facility, to be located in the southern corner of the Subject Lands adjacent to the future extension of Elliot Avenue, will provide water quality, erosion and quantity control for a drainage area of approximately 27.21 ha (refer to **Figure 5**). The SWM facility will have a permanent pool sized to provide 80% removal of total suspended solids to achieve an "Enhanced" level of quality control. Extended detention of the runoff from the Subject Lands during a 25 mm rainfall event will also be provided in the SWM facility for erosion control. Additionally, the SWM facility will have an outlet control structure designed to control post-development flows to pre-development levels for the 2 through the 100 year storm events for quantity control. The facility will discharge the 100 year post development controlled flows into the existing 1800 mm x 900 mm concrete box bypass sewer (Outlet 1) as outlined above (refer to **Figure 5**).

File #: 2655 December 20, 2024 Page 6 of 9

Proposed Sanitary Servicing

As outlined in the Functional Servicing and Stormwater Management Report (R.J. Burnside, February 2018) for the Storybrook Subdivision, there is an existing sanitary pumping station located within the Storybrook Phase 2A subdivision on Farley Road, approximately 100 m south of Kirvan Street. The sanitary pumping station was sized to accommodate a total peak flow of 73.5 L/s (6,108 persons), including Phases 2 and 3 of the Storybrook Development (refer to **Figure 1**). As per the Sanitary Pumping Station Design Report prepared by R.J. Burnside (dated December 2019), the anticipated drainage area for the Subject Lands was assumed to be 51.26 ha, which equated to 3,230 persons. This external drainage area included the Subject Lands, as well as additional external area from the lands to the north. Refer to **Attachment B** for Figure 1 from the SPS Design Report prepared by RJ Burnside (dated December 2019).

Sanitary sewer sizing along Elliot Avenue West and Farley Road throughout Phase 1 and 2 of Storybrook also accounted for this flow. A sanitary sewer stub was left as deep as possible (approximately 5.0 m) at the north limit of Elliot Avenue West at the interface of the Storybrook Subdivision and the Subject Lands. The pumping station wet well, process piping, forcemain, power supply, and control building were also all sized to accommodate the ultimate peak flow of 73.5 L/s, as per the SPS Design Report prepared by RJ Burnside (dated 2019).

The pumping station was previously upgraded to accommodate flows from the entire Storybrook Development, along with some additional residual flows from the Subject Lands. Further upgrades will be required to accommodate the ultimate condition that includes the entirety of the Subject Lands and additional external area, for which provisions were made during the design of the pumping station. To accommodate the ultimate scenario, with development of the Subject Lands, the current pumps will need to be replaced with two larger pumps (rated for 73.5 L/s) and a third "jockey" pump. The precast concrete top slab of the wet well may need to be reconfigured for the ultimate pump requirements. A larger generator (125 kW) will be required for these pumps, which the building has been sized for noting that the exhaust and gas supply have already been sized for the ultimate generator.

Following detailed design of Phase 2 and 3 of the Storybrook subdivision (refer to **Figure 1**), and due to intensification, the ultimate peak flow tributary to the pumping station will increase from 73.5 L/s to 83.0 L/s, if the same assumption for the Subject Lands and the external lands to the north is utilized (51.26 ha and 3,230 persons). Required pump upgrades will need to be confirmed by the pumping station designer. Based on the latest concept plan for the Subject Lands prepared by Weston Consulting dated January 1, 2025, the development is anticipated to have a net developable area of 29.0 ha with approximately 569 units. Based on a population density per unit of 3.04 (same as the Storybrook Subdivision), a population of 1,520 is expected, which is less than the originally anticipated 3,230 persons of capacity originally allowed for in

File #: 2655 December 20, 2024 Page 7 of 9

the downstream system. A more precise unit count and population can be determined once a more detailed plan is prepared in support of the Draft Plan of Subdivision application.

The site is proposed to be serviced via gravity sanitary sewers that will convey wastewater drainage to the existing sanitary stub at the north limit of Elliot Avenue West within the Storybrook Phase 2A+ lands. Sanitary sewers within the Subject Lands will be designed with a minimum cover of 3.0 m. The sewers will also be designed as per the following criteria, in line with the Township's Design Standards:

- Minimum pipe size: 200 mm diameter
- Minimum slope: 0.5%
- Minimum full-flow velocity: 0.8 m/s
- Maximum full-flow velocity: 3.0 m/s
- Average Daily Flow: 350 L/c/d
- Peaking factor as per the Harmon Formula
- Infiltration: 0.15 L/s/ha

Refer to the attached Conceptual Servicing Layout (Figure 6) for more details.

Proposed Water Servicing

The Fergus-Elora Water Supply System consists of a network of wells and interconnected feedermains, consisting of three pressure zones and four (4) elevated storage tanks for fire and peak flow, as discussed in the Water Supply Master Plan (prepared by AECOM, dated July 2019). The Subject Lands are entirely contained within Zone 1. The Aboyne Booster Pump Station transfers water via a 300 mm diameter trunk watermain from the Village of Elora to the Town of Fergus.

The Subject Lands are proposed to connect to the existing 200 mm diameter watermain on Elliot Avenue West, within the Storybrook Phase 2B lands (refer to **Figure 1**). Additionally, there is an existing 300 mm diameter watermain located on Beatty Line North, with a stub located at the intersection of Farley Road. Both connection points are within Zone 1. In order to connect at this location to provide looping for the site, a watermain approximately 350 m in length will be required from the east access point of the site, extending southeasterly along Beatty Line and connecting to the existing stub. Through previous correspondence with the Township, it is understood that the existing watermains should be sufficient to service the Subject Lands. Refer to the attached Conceptual Servicing Layout (**Figure 6**) for the location of the stub.

As per the Functional Servicing and Stormwater Management Report for the Storybrook Subdivision (R.J. Burnside, February 2018), there was an uncommitted residual capacity of approximately 2,451 units within the Fergus/Elora water system, while all three Phases of the Storybrook Development consisted of approximately 1,190 units. This suggests that there

File #: 2655 December 20, 2024 Page 8 of 9

should be available capacity within the system to service the anticipated 569 units within the Subject Lands. Additionally, the Township previously retained AECOM to undertake the Water Supply Master Plan study (dated July 2019), to assess the current and future demands of the Elora/Fergus water system up to the year 2041, and determine water supply alternatives to meet future needs. The study concluded that a new well location was being proposed directly north of the Subject Lands to meet the forecasted demands. While the Water Supply Master Plan initially indicated that this proposed well would be constructed in 2041, recent correspondence with the Township confirms that this well is anticipated to be constructed in 2026. The Township has indicated that they will provide further information on available capacity upon review of the OPA application.

Watermain within the Subject Lands will also be designed as per the following criteria, in line with the Township's Design Standards:

- Minimum cover: 2.0 m
- Minimum pipe size: 150 mm diameter
- Average and Maximum Daily Demand: 350 kPa to 550 kPa
- Minimum Hour and Peak Hour Demand: 275 kPa to 700 kPa

A future hydraulic analysis will be necessary to confirm the appropriate infrastructure sizing and configuration to provide adequate supply and pressure to service the proposed development and to confirm that the existing water storage and supply infrastructure is adequate to service the Subject Lands.

Summary

In summary, this PSSB has been prepared in support of the Official Plan Amendment application for the proposed residential development in the community of Fergus, in the Township of Centre Wellington. This brief outlines the means by which the proposed development can be graded and serviced in accordance with MECP, GRCA, and the Township of Centre Wellington design criteria and policies.

Minor and major system storm drainage from the Subject Lands will be directed by a storm sewer system and overland flow routes, respectively, towards a proposed SWM facility discharging to the existing 1800 mm x 900 mm concrete box bypass sewer located on Elliot Avenue, in the existing Storybrook Subdivision. External drainage contributing to the central wetland on-site will be captured and conveyed via a Clean Water Collector to the same outlet. The proposed SWM strategy will include a treatment train of LID measures and an end-of-pipe SWM facility providing quantity, quality and erosion control, in addition to water balance benefits.

File #: 2655 December 20, 2024 Page 9 of 9

This PSSB has shown that the site can be serviced from the existing municipal wastewater and water systems located east and south of the site, subject to the Township of Centre Wellington's confirmation of capacity and allocation.

We trust that this brief has provided sufficient level of detail on the proposed SWM and servicing infrastructure required for the proposed residential development to satisfactorily support the OPA application. Please contact the undersigned if you have any questions or require additional information.

Sincerely,

SCS Consulting Group Ltd.



Jamie Casey, P. Eng.

Encl.

Attachment A: Storm Servicing Background Information Attachment B: Sanitary Servicing Background Information

P:\2655 Sorbara - Brubacher\Design\Reports\OPA Servicing and SWM Brief\2655-OPA Preliminary Servicing and SWM Brief-20 December 2024.docx



Andrea Keeping, P. Eng. akeeping@scsconsultinggroup.com







File: P:\2655 Sorbara — Brubacher\Drawings\FSP\Fig\Report Figures\2655P—GRAD—5.0.dwg — Revised by <TMCNEIL> : Mon, Apr 08 2024 — 2:02pm





File: P:\2655 Sorbara - Brubacher\Drawings\FSP\Fig\Report Figures\2655P-SERV-3.0.dwg - Revised by <TMCNEIL> : Mon, Apr 08 2024 - 2:00pm

ATTACHMENT A STORM SERVICING BACKGROUND INFORMATION





LEGEND:							
STORYBROOK SUBDIVISION	202 CATCHMENT NUMBER	PROPOSED PARK BLOCK					
	24.01 CATCHMENT AREA (ha)	PROPOSED MEDIUM DENSITY BLOCK					
EXTERNAL AREA BYPASS STORM SEWER	PROPOSED SCHOOL BLOCK	EXISTING WOODLOT					
OVERLAND FLOW ROUTE	PROPOSED SWM FACILITY	PROPOSED COMMERCIAL					
MINOR FLOW CONTROLLED, MAJOR FLOW UNCONTROLLED							
MINOR FLOW UNCONTROLLED, MAJOR FLOW UNCONTROLLED	BURNSIDE	Figure Title STORYBROOK SUBDIVISION PHASE 1 PROPOSED DRAINAGE BOUNDARIES					
	Client	Drawn Checked Date Figure No.					
0 200 400 600 800 Metres	NIGUS FERGUS JOINT VENTURE INC.	Scale Project No.					
		H 1:5000 300031145					





LEGEND:





258m ³ OF LAYF APPROVED EQUIVA 100mm TI 0.25 DIA C 0.20 DIA P	FIELD LP-P10 (OR ALENT) OVERLYING TOPSOL AND SEED SP TILE DRAIN OUTLET INVERT-413.56 PVC TILE DRAIN OUTLET TOP OF 3055 FIELD DRAIN OUTLET TOP OF 3055	375# SAN 98m* 0° 1 PERRENX PERRENX MSTALL G PER 0° 50 7.2m-1800 BOX CULVE	PLUG 00-300mm# RIP-RAP 30mm DEEP VERLYING 2708 FILTER CLOTH OR EOUIVALENT XATE AS 804.050 804.0)R−35) 46.6m 0% / ₽VC L X+12X+12X+12X	-300# (SDR-35) =300 @ 1.10%	AGF 264m' OF LAYFIE - APPROVED EQUIVA - APPROVED EQUIVA	EXISTIN RICULTU Lent) overlying ND seed	G JRAL 	R-35) %	29.4m-250¢ PVC LEAD ●	(SDR-35) 1.50%		* 23-1 M + 1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	× cost and the state of the sta
existing differ to be fulled 4 3 PHASE 2B 2 2 2 2 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 2 1 2	BLOCK #225 TIDESEM BLEEKE MITOLF ROAD NSTRRUCTION COF ROAD TRUCTION TRUCTION M-3759 PVC SIM 0.0307 BLOCK 284 (0.300 RESERVE) TRUCTION TRUCTION STM 0.0307 BLOCK 284 (0.300 RESERVE) STM 0.0307 STM 0.0507 STM	200 201 201 201 201 201 201 201	RLCB-14.	© 275	© 274	C RLOB 13 TOP 415.09 E INV. 415.59 W INV. 415.57 S 273	S 272	© 271 DRIVE	S 270 270 12	© 269 26	B RC0E 15 NOP 415.80 NV. 414.44 3 267	266	265 LIMITOF CONSTRUC	ROAD
BH102 BH102 1509 WTB AHG BLO E	STM © 0.50% PLUC		H44 2000 SK3655 ST 54 F 90.0m-2000F 1509 PVC WATERWAR 2007 St 2007 St	1.30m (DBC SI VC STM 0 1.005 //// C SAN 0 1.30k				 € 673 € 673 € 73 1 1 8 9 8 9 9	665-8000 PVC STN 0 m-2009 PVC SAN 0 1509 PVC WA	2.907 9 ERMAIN F	ВИН42 61.9 ИН29А ИН29А ИН29А ИН29А ИН29А ИН29А В И ИН29А В И ИН29А В И ИН29А В И ИН29А В И И И И И И И И И И И И И И И И И И	M CONC SIDEWALK M 3000 PVC STAR 57.7m: 57.7m: 59m CNC SIDEWALK 59m CNC SIDEWALK FOR CONC SIDEWALK 59m CNC SIDEWALK FOR CONC SIDEWALK 59m CNC SIDEWALK	e 5.000 Dooe PV SAN e 5. COOE PV SAN E 5. COO	Tela Tela
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	B 245 DEPOSE OF E B B E E B B E E B B E E B B E E B B E E	S 246 2009 PV WATERW/ S S S S S S S S S S S S S	RR S S 247 241 CIN RR RF IN RR RF	S 3 249 RR	S S 250 25 RR सि	(S) 1 252 (R) (R)	S S 253 254 R R R	(S) 4 255 (RR) 	\$ 256 257 RR RR	S 258 2 RB C C C C C C C C C C C C C C C C C C	S S 59 260 R T R T T T			
L R L L R L R R L R R C R C R R C R C R	S R -243	Strid sam 18002		F RF L R R	(RF ^L ^R RF	 	 	S S 193 192 RF RF	© 191 1 (RF) (S S 90 189 P RP	S S 188 18 RF RF) (S) 7 186) (RF)	© (185 1) (€F) (€	S S S 84 183 182 P RF RF
L R Вновь L L R Вновь R С С С С С С С С С С С С С С С С С С	S R S C C C C C C C C C C C C C C C C C		4m-600¢ CDNC	130m CONC 511 130m C				73.8m-2009 PV				1.50m CONC \$10 (WL) 1.50m CONC \$10 (WL) 3 150m CONC \$10 (WL) 4	K V FVC WATERMAIN PVC WATERMAIN OF FVC SAN Ø Ø FVC SAN Ø	
$\begin{array}{c c} R \\ \hline \\$	© R − 239− − − © L ASE 2A+		200 C L R C L R C L R C R C C C C C C C C C C C C	 	S - S 2¢3 R - L R - R 	S S 204 R L R R R 	 	S S (206 2 R L R R R	S S 07 208 R R	S S 209 210 R R	© 211 R	S S 212 213 R R	S 214) €R	7.9m-3009 PVC_ STN ● 4.007 23.0m-3009 PVC_ STM ● 3.307 215 STM ● 3.3 7.5m-3009 P RR RR RR RR STM ● 3.3
L R R L R R L R R L R R C R R C R C R C			RF RF RF S R L S 229 L R R L R L R R	RF RF S S L R L R I I	RF RF ③ ⑤ 227 L R 	RF RF 3 226 L R	RF RF S S 225 L R I <td>R C C 2224 22 22 L R I</td> <td>F RF S S 23 222</td> <td>RF RF S S 221 220</td> <td>S C 219 CS 2</td> <td>S 218</td> <td>(S) 217</td> <td>AND AND AND AND AND AND AND AND AND AND</td>	R C C 2224 22 22 L R I	F RF S S 23 222	RF RF S S 221 220	S C 219 CS 2	S 218	(S) 217	AND
	S) R 0 236 - S) L 0 S R - 235 S L	19.6m 51M CBM/#63 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		O.507 O			n-5055/20hic stm @ n-2005 ² 7VC san @		NH40A	277 @. @ 277 de. 2m - 52 54 (50 de. 1m - 200€ PV de. 150₽ PVC WA D //// de. 150₽ PVC WA D //// de. 150₽ PVC WA	62/3TM 6/20/5642	7.1m-37; STM @ 1.50m CONC SOEWAL 1.50m CONC SOEWAL 1.50m CONC SOEWAL	50 PVC 1.502 BMH00 BMH00 C BMH00 C C C C C C C C C C C C C	RF 170
L R L L L L R L L R L L L L R L L R L L R L L R L L R L L R L L R L L L R L L R L	S R -234	200# PVC	 		© © ® 156 ® 156 R L	 	€	POVEY RO	AD (5) (5) 161 162 (7) (7) (7) (7) (7) (7) (7) (7)	© 163 R	\$ \$ 164 165 PP PP	্ড 166 (हिन्नि	© (167 1। सिम् (ह	(RF) (S) 169 (S) 68 (R) (R)
$\begin{array}{c c} L \\ R \\ \hline \end{array} \\ \hline \\ \\ \hline \end{array} \\ \hline \end{array} \\ \hline \end{array} \\ \hline \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \hline \\ \\ \hline \end{array} \\ \\ \\ \hline \\ \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \\ \\$	C O N S S S S S S S S S S S S S S S S S S		STRUCTION Sala La	RE				PHASE						
	17.0m-375ø PVC_	2006 WATE		S	RF RF S S	RF R	F) (RF) (3) (S)	PHASE RF RF S S	2A RF S S	RF RF S S	RF S S	RF RF S S	F) RF (
PHASE 2B BHIII BHIII Some 1500 1500	12.5m-975¢ CONC STM © 0.302 STM © 0.302 CK 28.3 CK 28.	Ver 20000 2000	VIE AND DISPOSE OF ORARY BARRICADE - 5250 COLO - 1403 - 2500 COLO - 1403 - 2500 PVC WATER - 2500 PVC WATER - 1500 PVC WATER - 1500 PVC WATER - 1500 PVC WATER	90.0m-2d0e PV5 MAIN	RF RF S S S S S S S S			PHASE RF RF S S STREET 9222 10-2009 P% SN 0 11-2009	2A (RF) (RF) (S) (S) 0100000000000000000000000000000000000			RF RF S S m-300/2010 SAN @ S 2000/PVC SAN @ S	F) (RF) (3) (S) (1) (S) (10 (S) (11 (S) (12 ((13 ((
PHASE 2B BH111 BH11BH11	17.0m-3756 PVC 12.5m-9756 CONC STM 0 0.302 CK 283 OCK 283 OCK 800 State 2000 State 2000 STM 0 0.502 State 2000 State 2	4 4 4 4 4 4 4 4 4 4 4 4 4 4	Image: Second	© 0.0m 2000 PV05 90.0m 2000 PV05 MAIN A 1000000000000000000000000000000000000	RF S RF S RF S RF S REF PHA FOR	RF S S C C C C C C C C C C C C C C C C C	B RF C SPICER	РНАЗЕ (RF) (RF) (S) STREET 5500 P% 5410 11-2000 P% 5410 11-2000 11-2000 11-2000 11-2000 11-2000 11-2000 11-2000	2A (FF)	RF S S RF S S S S S S S S S S S S S S S		RF RF S S m-3006/29/C STM S 2000 PVC SAN @ PVC HEXAL PVC RR S S S	E) (RF) () (S) (S) () (S) (S) () (S) (S) (S) (S) (S) (S) (S) (S) (S)	460.5m - 975/mm ST - 2508/047 - 2
PHASE 2B BHIII BHIII ISOS ISOS IS IS IS IS IS IS IS IS IS IS IS IS IS	17.0m-3756 PVC 12.5m-9756 CONC STM 00.302 OCK 283 OCK 800 2006 SAN PLUG PLUG PLUG STM 00.502 ST 2006 SAN PLUG SAN 0.500 FVC SAN 0.000 CONC BOX CWC 0.0302 BOX CWC 0.0302 SAN 0.000 CONC BOX CWC 0.0302 SAN 0.000 CONC BOX CWC 0.0302 SAN 0.000 CONC BOX CWC 0.0302	4 00000 000000 FEEM 1.0000000 FEEM 1.00000000 FEEM 1.00000000 FEEM 1.000000000 FEEM 1.000000000000000000000000000000000000	VE AND DISPOSE OF ORARY BARRICADE 1-5259 CONC 01.402 01.402 0200000 01.402 01.4	© 0.0m 2000 PVC MAIN C C C C C C C C C C C C C C C C C C C	RF RF S RF S RF RF REF FOR	RF S CONTIN CONS RF	RF SPICER	PHASE RF S S S S S S S S S S S S S	2A (FF) (S) (S) (S) (S) (S) (S) (S) (S	RF RF S S Image: state stat	RF RF S	RF RF S S 19/22/10 S 10/22/22/10 SAN 0 10/22/22/20 REMOVE CALL 10/22/20 ROVE REMOVE S 0 RP S S	P (RF) B (S) (1) (S) (1) (S) (C) (C) (C) (C) (C) (C) (C) (C	⁴ 60.5m - 975mm STM @ 0.905 3 1 1 1 6.6m - 975mm 1 1 1 6.6m - 975mm
RE-GRADE TO FILL IN DITCH AS PART OF PHASE 2B WORKS 0.15 DIA CSP BOX CVC 0.50 DIA CSP BOX CVC 0.50 DIA CSP BOX CVC 0.50 DIA CSP BOX CVC 0.50 DIA CSP CVC 0.50 D	17.5m-3756 PVC 12.5m-9756 CONC STM 0 0.302 CK 28.3 OCK 28.3	A Constraints of the second se	WE AND DISPOSE OF ORARY BARRICADE 5259 CONC 01.403 01.403 01.403 01.403 01.403 0200000 1.103 0200000 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1003 0.1004 0.1005 0.1005 0.1007 0.10	S S S S S S S S S S S S S S S RP S RF S	RF RF S RF S RF S RF RF RF RF RF RF RF S RF S RF RF RF	RF (R) S (S) CONTIN CONS RF (S) S (S) S (S) RF (S) S (S)		PHASE RF RF S S S	2A (FF)	RF RF S S Image: state stat		RF RF S S 1 2000	Ref Ref S Ref S Ref S	40.5m - 975mm STM @ 0.902
PHASE 2B BHIIII BHIIII BHIII BHIII BHIII BHIII BHIIII BHIIII BHIIII BHIIII BHIII BHIII BHIII BHIII BHIII BHIII BHIII BHIII BHIII BHIII	17.5m-3756 PVC 12.5m-9756 CONC STM 0 0.302 CK 283 OCK 283 OCK 283 OCK 283 CM 0 0.502 # 2006 SAM PLUG TM 0 0.502 # 2006 SAM PLUG STM 0 0.502 # 2006 SAM PLUG STM 0 0.502 # 2006 SAM PLUG SAM 0 0.502 # 2006 SAM PLUG SAM 0 0.502 # 150 PPVC SAM 0 0.502 # 100 000 000 CM SAM 0 0.502 # 100 000 000 000 000 CM SAM 0 000 000 000 000 CM SAM 0 000 000 000 CM SAM 0 000 000 000 000 000 000 CM SAM 0 000 000 000 000 000 000 000 000 000	All and a second	NEE AND DISPOSE OF OWEANY BARRICADE 1-52559 CONC OF OWEANY BARRICADE 1-52559 CONC 01.4002 1000000000000000000000000000000000000	S 2255 <t< td=""><td>RF RF S RF S RF S RF RF RF FOR RF RF RF S RF RF RF RF RF</td><td>RF (* S (* C (* C (* S (* C (* C (* C (* C (* S (* C (* C</td></t<> <td></td> <td>PHASE RF RF S S S</td> <td>2A (FF) (S) (S) <!--</td--><td>RF RF S S Image: second secon</td><td>RF RF S S Image: Signature strategy of the st</td><td>RF RF S S 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007</td><td>R R</td><td>460.5m 975mm 8 2 15005Wai 3 2 15005Wai 3 3 1 16.6m 975mm 55.7mm 3 3 1 16.6m 975mm 55.7mm 3 3 1 16.6m 975mm 55.7mm 3 3 2 14.8m 975mm 55.7mm 3 3 1 16.6m 975mm 57.7mm 3 3 2 14.8m 3 3 3 3 1 1.6m 3 2 4 3 5 8 5 8 5 8 5 8 5 8 5 8 5 8 5 8</td></td>	RF RF S RF S RF S RF RF RF FOR RF RF RF S RF RF RF RF RF	RF (* S (* C (* C (* S (* C (* C (* C (* C (* S (* C		PHASE RF RF S S S	2A (FF) (S) (S) </td <td>RF RF S S Image: second secon</td> <td>RF RF S S Image: Signature strategy of the st</td> <td>RF RF S S 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007</td> <td>R R</td> <td>460.5m 975mm 8 2 15005Wai 3 2 15005Wai 3 3 1 16.6m 975mm 55.7mm 3 3 1 16.6m 975mm 55.7mm 3 3 1 16.6m 975mm 55.7mm 3 3 2 14.8m 975mm 55.7mm 3 3 1 16.6m 975mm 57.7mm 3 3 2 14.8m 3 3 3 3 1 1.6m 3 2 4 3 5 8 5 8 5 8 5 8 5 8 5 8 5 8 5 8</td>	RF RF S S Image: second secon	RF RF S S Image: Signature strategy of the st	RF RF S S 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2006 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007 1 2007	R R	460.5m 975mm 8 2 15005Wai 3 2 15005Wai 3 3 1 16.6m 975mm 55.7mm 3 3 1 16.6m 975mm 55.7mm 3 3 1 16.6m 975mm 55.7mm 3 3 2 14.8m 975mm 55.7mm 3 3 1 16.6m 975mm 57.7mm 3 3 2 14.8m 3 3 3 3 1 1.6m 3 2 4 3 5 8 5 8 5 8 5 8 5 8 5 8 5 8 5 8



ATTACHMENT B

SANITARY SERVICING BACKGROUND INFORMATION



